

2-Wire Analog Telephone and/or RS-485/RS-422 FOM II Modems

F27xxA
F27xxAD

Selection Guide

Model	Description
F2702A	2-wire; single channel; 14.4Kbps: analog line; 2km; LC connectors; 1310nm; multimode; Exchange side
F2712A	2-wire; single channel; 14.4Kbps: analog line; 2km; LC connectors; 1310nm; multimode; Subscriber side
F2705A	2-wire; single channel; 14.4Kbps: analog line; 20km; LC connectors; 1310nm; singlemode; Exchange side
F2715A	2-wire; single channel; 14.4Kbps: analog line; 20km; LC connectors; 1310nm; singlemode; Subscriber side
F2702AD	2-wire; single channel; 14.4Kbps: analog line; 2km; LC connectors; 1310nm; multimode; Exchange side; RS-422, RS-485 to 64Kbps
F2712AD	2-wire; single channel; 14.4Kbps: analog line; 2km; LC connectors; 1310nm; multimode; Subscriber side; RS-422, RS-485 to 64Kbps
F2705AD	2-wire; single channel; 14.4Kbps: analog line; 20km; LC connectors; 1310nm; singlemode; Exchange side; RS-422, RS-485 to 64Kbps
F2715AD	2-wire; single channel; 14.4Kbps: analog line; 20km; LC connectors; 1310nm; singlemode; Subscriber side; RS-422, RS-485 to 64Kbps