

MSI - PoE Mid-Span Injector

Technical Specifications

Standards:	IEEE 802.3af
RJ-45 In Jack:	Shielded RJ-45 Ethernet, Fast Ethernet, and Gigabit Ethernet Cables: Cat5, Cat5e, Cat6
RJ-45 Out Jack:	Shielded RJ-45 PSE Pins: 4, 5, 7, 8 Ethernet, Fast Ethernet, and Gigabit Ethernet Cables: 4-Pair Cat5, Cat5e, Cat6
PoE PSE:	PSE Pins 4/5: Positive 48VDC PSE Pins 7/8: Negative 48VDC Power delivery up to 15.4W max.
Protection:	Incompatible PD Detection, Disconnection Overload, Over-Current, Short Circuit, Under Voltage
LED Indicators:	Power Status
Power Input:	DC IN Jack for External Power Adapter Input Voltage: 48VDC, 0.4A min. (MSI-PS included with unit)
Environment:	Operating Temperature: -5° C ~ 50° C Storage Temperature: -20° C ~ 80° C Humidity: 5% ~ 95% non-condensing
Dimensions:	1.97 x 3.15 x 0.83 inches (50 x 80 x 21 mm)
Approval:	FCC Class B, CE Class B, CISPR 22 Class B