

# 6-Port 10/100/1000 Industrial Managed Switch with (1) SFP Slot

SF70660M

## Product Models

Model	Description
SF70660M	6-Port 10/100/1000 Industrial Managed Switch, (1) SFP Slot
PMB-2	SF70660M Panel Mounting Kit
DRB-1	SF70660M DIN Rail Mounting Kit
PSAC08	SF70660M Power Supply, 100-240VAC to 12VDC/1A
SFP Modules	VERSITRON 1000Base Fiber Optic SFP Modules

## Technical Specifications

<b>Standards:</b>	IEEE 802.3, 802.3u, 802.3ab, 802.3x, 802.1Q
<b>Network Ports:</b>	(5) 10/100/1000Mbps Ethernet Copper Ports (Shielded RJ-45) (1) 100/1000Mbps SFP Slot
<b>VLAN:</b>	Port-based VLAN, 802.1Q Tag-Based VLAN
<b>QoS:</b>	4 priority queues, Classification: Port-based, 802.1Q, IP DSCP
<b>Network Cables:</b>	Copper Port: 10/100Mbps: Cat5 up to 100 meters 1000Mbps: Cat5e or higher up to 100m SFP Slot: 50/125, 62.5/125 MM Fiber, 9/125 SM Fiber
<b>Buffer Memory:</b>	112KB
<b>MAC Addresses:</b>	Table with 8K entries
<b>LED Indication:</b>	Display on both top and front panels Per unit: Power, Per Port: Speed, Link/Activity & Optical Link for SFP Slot
<b>Management Support:</b>	Web browser software, management VLAN ID
<b>DC Power Input:</b>	Screw terminal block: +5VDC ~ +30VDC DC Jack: +7.5VDC/1A (-D6.3mm / +D2.0mm)
<b>Power Consumption:</b>	3.6W max. @ +7.5V input
<b>Environment:</b>	Operating Temperature: -20° C ~ +74° C Storage Temperature: -20° C ~ +85° C Relative Humidity: 10% to 90% non-condensing
<b>Dimensions:</b>	5.67 x 4.11 x 1.02 inches (WxDxH)
<b>Approvals:</b>	FCC Class A certificate, CE mark/EMC Class A certificate EN60950/IEC60950-1 safety NEMA TS2-2003 Environment tests