

# 4-Port 10/100/1000 Ethernet Switch with (2) 1000Base SFP Slots

SG70460

## Technical Specifications

<b>Standards:</b>	802.3u, 802.3z, 802.3ab
<b>MAC Address Table:</b>	1K
<b>Frame Buffer Memory:</b>	512Kb
<b>Switching Capacity:</b>	8Gbps
<b>Connectors:</b>	Copper Port: RJ-45 Fiber Ports: SFP Modules with LC Connectors
<b>Cables:</b>	Copper Port: Cat5 or Higher Fiber Ports: Multi-Mode: 50/125 or 62.5/125 Single-Mode: 8/125 or 9/125
<b>Flow Control:</b>	Full Duplex: 802.3x Flow Control Half Duplex: Back Pressure Flow Control
<b>LED Indicators:</b>	Power Copper Port: Link/Activity, Speed Fiber Ports: Link/Activity
<b>Power Requirements:</b>	Power Supply Input: 100-240VAC, 50~60Hz Power Supply Output: 5VDC, 3A
<b>Environment:</b>	Operating Temperature: 0° C ~ +50° C Storage Temperature: -20° C ~ +70° C Humidity: 5% ~ 90% non-condensing
<b>Dimensions:</b>	4.92 x 3.35 x 1.06 inches (L x W x H) 125 x 85 x 27 mm (L x W x H)