

The **VERSIMUX II** with the latest product enhancements can accommodate the following:

| Analog Telephone | Data Signals |
|--|--------------------------------|
| 1-Channel of 2-Wire Telephone | RS-232, RS-423 |
| 1-Channel of 2-Wire Telephone with RS-485/RS-422 Data | RS-530, RS-422 |
| 4-Channels of 2-Wire Telephone | RS-449, V.35, MIL-STD-188-114A |
| 4-Channels 2-Wire of Telephone with RS-485/RS-422 Data | T1, E1 |
| 8-Channels of 2-Wire Telephone | 1-Channel of Stereo Audio |
| 1-Channel of 4-Wire Telephone | 2-Channels of Mono Audio |

VERSIMUX II Product Models: Analog Telephone Port Cards

| Model | Description |
|---------|--|
| F270xA | 1-Port of 2-Wire Telephone Exchange Side Card |
| F271xA | 1-Port of 2-Wire Telephone Subscriber Side Card |
| F270xAD | 1-Port of 2-Wire Telephone Exchange Side + 1-Channel RS-485/RS-422 Card |
| F271xAD | 1-Port of 2-Wire Telephone Subscriber Side + 1-Channel RS-485/RS-422 Card |
| VMX4E | 4-Ports of 2-Wire Telephone Exchange Side Multiplexer Card |
| VMX4S | 4-Ports of 2-Wire Telephone Subscriber Side Multiplexer Card |
| VMX4ED | 4-Ports of 2-Wire Telephone Exchange Side + 1-Channel RS-485/RS-422 Multiplexer Card |
| VMX4SD | 4-Ports of 2-Wire Telephone Subscriber Side + 1-Channel RS-485/RS-422 Multiplexer Card |
| VMX8E | 8-Ports of 2-Wire Telephone Exchange Side Multiplexer Card |
| VMX8S | 8-Ports of 2-Wire Telephone Subscriber Side Multiplexer Card |
| F272xB | 1-Channel of 4-Wire Telephone |
| VMX4800 | VERSIMUX II Telephone Multiplexer SmartCard |

VERSIMUX II Product Models: Data Port Cards

| Model | Description: Serial Data Port Cards |
|--------|---|
| F2242x | 1-Channel of T1/E1 Fiber Modem (1.544Mbps/2.048Mbps) |
| F272xB | 1-Channel of Mono Audio or 2-Channels of Stereo Audio |
| F280xD | RS-232 Data (also supports RS-423 and MIL-STD-188-114A (Unbalanced)) |
| F282xD | RS-530 Data (also supports RS-422, RS-449, V.35, and MIL-STD-188-114A (Balanced)) |

VERSIMUX II Product Models: Accessories

| Model | Description |
|---------|---|
| HF-1 | Standalone Single-Card Enclosure |
| HF-2SS | 2-Slot, 19" Rack-Mount Chassis (1U) |
| VMX20 | 20-Slot, 19" Rack-Mount Chassis (4U) |
| AC300WR | Redundant Power Supply/System Monitor for VMX20 Chassis |
| PSAC20 | 120VAC to 12VDC/2A Power Supply for VMX4x & VMX8x Multiplexer Cards |
| PSAC08 | 120VAC to 12VDC/1A Power Supply for F27xxxx & F28xxD Modems |
| PSAC09 | 230VAC to 12VDC/1A Power Supply for F27xxxx & F28xxD Modems |

VERSIMUX II Product Models: SFP Modules

| Model | Application | Wavelength | Max. Distance | Fiber |
|---------|--|------------|---------------|-----------|
| FE2MM | VERSIMUX II 4-Port & 8-Port Installations | 1310nm | 2 km | Duplex MM |
| FE10SM | VERSIMUX II 4-Port & 8-Port Installations | 1310nm | 10 km | Duplex SM |
| 3GBMM | VERSIMUX II High Density Installations | 850nm | 160 m | Duplex MM |
| 3GB20SM | VERSIMUX II High Density Installations | 1310nm | 20 km | Duplex SM |